

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number  
WO 2004/026437 A1

(51) International Patent Classification<sup>7</sup>: B01D 35/147,  
35/30, 29/15

NTZ Nederland BV, Sydneystraat 60, NL-3047 BP Rotterdam (NL). BORGER, Ron [NL/NL]; NTZ Nederland BV, Sydneystraat 60, NL-3140 AA Rotterdam (NL).

(21) International Application Number:

PCT/IB2003/004079

(81) Designated States (*national*): AU, BR, CN, IN, JP, KR, MX, US.

(22) International Filing Date:

19 September 2003 (19.09.2003)

(84) Designated States (*regional*): European patent (BE, DE, DK, ES, FR, GB, IT, NL, SE).

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02078889.9 19 September 2002 (19.09.2002) EP

**Declarations under Rule 4.17:**

- as to the identity of the inventor (Rule 4.17(i)) for the following designations AU, BR, CN, IN, JP, KR, MX, European patent (BE, DE, DK, ES, FR, GB, IT, NL, SE)
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AU, BR, CN, IN, JP, KR, MX, European patent (BE, DE, DK, ES, FR, GB, IT, NL, SE)
- of inventorship (Rule 4.17(iv)) for US only

**Published:**

- with international search report


(71) Applicant (*for all designated States except US*): NTZ NEDERLAND BV [NL/NL]; P.O. Box 25, Sydneystraat 60; 3047 BP ROTTERDAM, NL-3140 AA Maassluis (NL).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): NIEWLAND, Pierre, Gerard [NL/NL]; P.O. Box 25, NL-3140 AA Maasland (NL). SCHAEERLAECKENS, Willy [NL/NL];

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: MICRO FILTER DEVICE FOR AN IN LINE FILTERING CONFIGURATION



(57) Abstract: Oil Filtering device (1) comprising a micro filtration filter element (20, 22) having micro-filtration means (20), and comprising a filter housing (16) and a lid part (17) of said housing (16), tightening means (10) for pressurised interconnection of said lid (17) and housing, the device comprising an oil inlet port (3) and an oil outlet port (9) in connection with a cylindrical interior space (21) of said filter par (5; 20). The filtering device is provided with a by pass means (25,28) formed by an aperture (28) such as a bore, provided in a closing member (24) for the filtration means, the aperture connecting the space in the device exterior to the filter part to an interior space (21) such that during operation of any system in which the device is incorporated, a minimum flow of oil through the filter device is secured by said by pass means.

WO 2004/026437 A1

## MICRO FILTER DEVICE FOR AN IN LINE FILTERING CONFIGURATION

5           The present invention relates to a filter device as defined in the preamble of claim 1.

Such devices are generally known and commonly are provided with a filter part for filtering particles from oil that has contacted rotational parts such as in transmissions, and which even may have been used for lubricating engines. With  
10 nowadays increase in engine powers, the increased use of automatic transmissions with torque converters, and with the increasing refinement in valve components within such hydraulic systems it has become a desire to have refined the filtration of the oil to a considerably increased amount, i.e. by so called micro filtration. Such desire also emanates from a public convenience desire of not needing to change oil in cars, at  
15 least to have such need to a much lesser extend.

Micro filtration as such, and its effect as compared to conventional filtering is know per se, e.g. from SAE paper 2001-01-0867 "Automatic transmission hydraulic system cleanliness - the effects of operating conditions, measurement techniques and high efficiency filters", which document is hereby regarded included. Micro filters per  
20 se are also know, e.g. from international patent application PCT/NL00/00530 which is also regarded included. The known micro filter consists of radially wound more or less relatively highly compressed cellulose fibres. This type of micro filter is suitable for and known from application in a so called by pass configuration. In such a configuration the original filter of the hydraulic system remains in its original position in the flow system,  
25 i.e. remains in a so called in line arrangement, while independent from the main hydraulic stream, an auxiliary hydraulic loop is created, in which the micro filter is incorporated. The auxiliary loop may e.g. consist of only a minor part of the entire hydraulic flow, e.g. 10%. Yet, in this manner, over time this configuration effects a gradual decrease of degree of contamination of the oil up to the level of the filtering  
30 grade the micro filter. With a micro filter as known, a fill for life for passenger vehicles may be accomplished, especially since a large amount of filtered particles may be accommodated in the filter due to a relatively extremely large radial thickness of the filter material on the one hand, and on the other hand because a low degree of contamination of oil tends to slow down further contamination thereof. The requirement  
35 for an additional hydraulic flow and an additional filter device, thus for increased initial

costs, has in automotive applications up to now hampered wide spread adoption of the micro filter, despite its advantages.

It is therefore an object of the present invention to provide a solution enabling the use of a micro filter in an in line configuration, be it with lowest amount of effort, with  
5 lowest amount of initial costs, or with optimised functionality of the micro filter. According to the invention such has been realised with the measures as defined in the characterising portion of claim 1.

According to the invention, micro filters of a relatively very fine filtering grade, as well with a relatively high filtering efficiency may be applied by using a device which is  
10 at least at one end provided with a separate oil flow closing member contacting an end face of the filter part at one axial end. An improved Filter device is realised in that the filtering device is provided with a by pass means, such that during operation of any system in which the device is incorporated, a minimum flow of oil through the filter device is secured by said by pass means.

15 The by pass means is formed by an aperture such as a bore, provided in a closing member connecting the space in the filter device exterior to the filter part to an interior space of said filter part for receiving oil radially passed through the filter and for receiving any oil passed through said aperture. In this way the by pass flow may be better controlled, while leaving the closure of the axial end faces in tact at all time,  
20 which is of advantage because any debris gathered here tends to loosen relatively easily, so that part of the filtered material would otherwise, be it with the security of return into the filter over time, re- entered into the oil flow. This solution secures a base flow of oil, while at increasing operating pressures, a relatively larger part of the flow passes through the micro filter

25 The invention will now be elucidated further along a drawing in which:

Figure 1 schematically represents a filter device integrated with an oil cooler device;

Figure 2 represents a cross section of a first modification of a filter device according to the invention, allowing the replacement of a conventional filter part by an  
30 e.g. cellulose fiber based, ultra fine grade filter, i.e. within the existing housing of said conventional filter, enabling both after sales replacement and factory based replacement;

In the figures, identical reference numbers relate to identical or at least comparable technical features.

Figure 1 schematically represents a filtering device 1, applied in combination with an oil cooling device 2. The device 1 is provided with a housing 3, opened at one side that is pressingly attached, here by bolts 10, to a cooler device 2. It may either be connected directly to the housing of the cooler 2, or indirectly via a base plate not depicted, to which both devices are then attached. The filter device 1 is fed via an inlet port 3 connected via a bore 4 to an outlet port of the cooler device. The cooler receives heated oil, e.g. by an engine or a transmission, via an inlet port 6. The oil is cooled while being fed through the cooler device, which is in turn cooled by a preferably liquid cooling agent, running through a separate channel system, having an inlet port 7 and an outlet port 8. The cooled oil received by the filter device 1 is radially forced through the cylindrically shaped filter part 5 of which one axial end is closed, while the other end connects to a discharge port of the filter device. The device is provided with tightening means in the form of bolts 10, which has the advantage that a filter part 5 within the housing may be clamped against the lid without the latter being possibly affected by any rotational movement. However, the lid may in principle also e.g. be connected to the house by a threaded provision for a mutually screwed connection.

Figure 2 more in detail depicts a cross section of the filter device 1 of figure 1, however fitted with an ultra high efficiency filter for micro filtration within a generally known housing as suited for a conventional, e.g. in line filter, typically allowing a high throughput of oil and capable of filtering particles of e.g. 20  $\mu\text{m}$  and larger. Micro-filtration typically is capable of filtering particles of 0,5  $\mu\text{m}$  and larger. Rather than at conventional filters, which only, or at least mainly are based on a sieving principle, this result is possible since micro filtration is based both on sieving and on a polarity or binding principle where contaminations are bound to fibres. In casu the filter applied is capable of filtering particles of 0,5  $\mu\text{m}$  and up. One type of micro filter that may be used for the present purpose is a cellulose based filter. The housing for such conventional filter part shows an outlet port 9 accommodated in a tube shape, integrally shaped with a thickened support part 11 of the relevant wall part 12 of the housing, in casu the wall part 13 oriented axially in relation to the cylindrical filter part. In conventional application this support part 11 functions as a support for both an O-ring fitting the transition from the support base to the tube part 10. In such conventional application The O-ring in turn supports the relevant axial end of the filter part. The inlet port 3, associated with a bore or tube 4 not depicted in this figure, is

provided in a locally widened housing part 3A of the filter device. The bore or tube 4 may be provided either in the lid part 17 of the housing or in the main housing part 16.

In the embodiment according to figure 2, the use of a micro filter within the structure adapted for receipt of conventional, in line oil filters is enabled by the provision of a rigidly formed filler part 14 and a large diameter O-ring fitting into the space between the thickened wall part 11 and a radial housing part 16, filling the space between the axial wall part. The filler part 14 simultaneously forms an axial end closure to the micro filter part 20. An axial end wall of the filter part stretches in a plane oriented transversely to the axial direction of the filter part. The filter part 20 is formed with a filter of which the radial thickness is substantially larger than the radius of the cylindrical inner space 21 of the filter part. The central space 21 is formed by a perforated tube part 22 forming an internal wall of the filter part 20. The other axial end of the filter part is also closed for oil passage by an other end closure member 24, also rigidly shaped and also provided separate from the filter part 20. The closure members 14, 24 are pressed against the relevant end faces of the filter part under the influence of a rigid connection between the filter housing and relevant wall part 17 associated with the cooler device 2, and of a close tolerance fitting of the relevant parts, thereby relying on a fractional axial deformation capacity of such cellulose material based filter part. An advantage of the current filtering arrangement is that the housing 16 may entirely remain unchanged. This in turn enables both the after market application of a micro filter 20 and an easy to implement factory mounting of a micro filter 20.

Also for accommodating less strict tolerances, thereby reducing manufacturing costs, a spring member 25 may be provided between the wall part 17 and the closure member 24. For the purposes of enhancing proper positioning of the filter part 20, a dimple 26 may be provided in the wall part 17, receiving part of the closure element and preferably the spring device 25. In the depicted sophisticated embodiment of this feature, the closure element is provided with a small, axially exterior part that is of radially smaller width, such that the spring element may be received and straight guided by the thus created opening or groove between the dimple and said closure part. Preferably the spring is of a diameter at least almost corresponding to the outer diameter of the closure element 24, which in turn, the other closure member 14, has a diameter corresponding to that of the filter part. In this manner a relatively thick and highly loadable spring may be accommodated. The arrangement with said dimple 26 provision also positively influences the axial length of the filter part 20. Both closure elements are preferably provided with a generally

cylindrical notch 27 fitting the internal space 23 of the filter device. The notch 27 of the closure member 14 connecting to the outlet port 9 is provided with a central bore for oil discharge. Especially in case the device is provided with a spring means 25, the closure members 14, 24 and the contacting faces 16AF and 16BF as described at the following figures, are preferably provided with concentric ribs which are pressed into the material of the end face 20F of the filter part 20.

In accordance with a further aspect of the invention, the filtering device is fitted with a spring member 25, while the relevant, outlet 9 opposing closure member 24 may also be provided with a bore, either fully open or fitted with a pressure dependent valve member known per se and not depicted in the figure. The filter device 1, when thus provided with a bore only, is adapted as a by pass filter system, securing a base flow of oil that is directed through the bore. At relatively high pressures, when the oil flow may not fully pass through the bore, it passes radially through the filter part 20. In this manner the filter device functions as a by pass filtering system at relatively high pressures only. Yet, in practice if at least a part of the oil passes through the micro filter, the oil will in time gradually become entirely filtered, i.e. will become cleaner up to the level determined by the chosen filtering grade. The diameter of the bore may be varied in accordance with the desired base flow and the desired percentage of oil passing through the filter part 20 per unit of time, taking into account the chosen specifications of the filter part 20.

The filter device according to this further aspect of the invention may also be provided with a valve member fitted to the above mentioned bore. In this manner a filter device is created for securing an additional oil passage in addition to the oil passage through the filter part 20, given a certain pressure at which the oil is provided to the filter part 20. The valve member accommodated according to the invention opens wider with increasing pressure. Such pressure dependent valve member enhances certain applications or certain operating conditions where a micro filter may not allow for a sufficient flow as often required by so called in-line filter applications. The filter device according to the invention then operates as a by-pass filter, accommodated in a typical in-line filtering arrangement. Typically such valve member known per se is composed of an elastically deformable synthetic material, having a tube part with an inner cylindrical opening at one end, gradually changing into a rectangular like, and subsequently line like opening at the other end, which without internal oil pressure acting on it is closed by internal wall parts being pushed against each other. This end part of the tube may open under oil pressure under a resistance

force acting against elastic deformation emanating from the combination of the particular shape and the elastically deformable nature of the material. Therefore, depending on the desired guaranteed flow rate at any pressure level, depending on the specifications of the filter, such as radial thickness, axial length and filtering grade,  
5 the valve member may be designed in accordance with a manufacturers wish.

The invention, apart from the following claims, also relates to the preceding description and all details and aspects in the drawing which are directly and unambiguously derivable there from, at least by a man skilled in the art.

**CLAIMS**

1. Oil Filtering device (1) for filtering oil used in rotational devices such as engine and transmission, comprising a micro filtration filter element (20, 22) having micro-  
5 filtration means (20), the element having an interior space (21) , and the device comprising a filter housing (16) and a lid part (17) of said housing (16), tightening means (10) being provided for pressurised interconnection of said lid (17) and the housing (16), the device (1) comprising an oil inlet port (3) and an oil outlet port (9) in connection with a cylindrical interior space (21) of said filter part (5; 20; 20A-20D),  
10 characterised in that the filtering device (1) is provided with a by pass means (25, 28) formed by an aperture (28) such as a bore, provided in a closing member (24) for closing off an axial end face of the filtration means (20), the aperture connecting the space in the filter device (1) exterior to the filter part (20, 20A-D) to an interior space (21) such that during operation of any system in which the device (1) is incorporated, a  
15 minimum flow of oil through the filter device (1) is secured by said by pass means.
2. Filter Device (1) according to any of the preceding claims, characterised in that the device (1) comprises a filter part (5; 20; 20A-20D) of which the radial thickness of its filter means is larger than the radial thickness of its interior space, the axial end faces (20F; 20AF-20DF) of the filter part (5; 20; 20A-20D) being formed by the filtering  
20 means of said part, and the device (1) being provided with internal, essentially flattened filter end face (20F; 20AF-20DF) contacting faces (14F, 24F, 16AF, 16BF, 17F), for axially closing a passage of oil, and having a diameter matching that of the filter part (5; 20; 20A-20D).
3. Filter Device (1) according to the preceding claim, characterised in that an oil  
25 passage closing face (16AF, 16BF) is integrated in a housing part (16A, 16B, 17).
4. Filter device (1) according to the previous claim, characterised in that an oil passage closing face (16AF, 16BF) is integrated in a housing wall part having a thickness of more than twice the thickness of the majority of the wall part of a relevant unit (16) of the housing (16, 17).
- 30 5. Filter device (1) according to any of the previous claims, characterised in that the closing face is integrated in an insert member (14) fitting irregularities in shape of a relevant part (11) of the housing (16) at an axial side of the insert (14) opposing the closing face (14F), and preferably being provided with an O-ring corresponding to the largest diameter of the insert member (14).



6. Filter device (1) according to any of the preceding claims, characterised in that the device is at least at one end provided with a separate oil flow closing member (24), contacting an end face of the filter part at one axial end and contacting a housing part (17) via a spring loaded means (25).

1/1




FIG. 1




FIG. 2

## INTERNATIONAL SEARCH REPORT

Intern. Application No  
PCT/EP 03/04079

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B01D35/147 B01D35/30 B01D29/15

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 737 502 A (KNECHT FILTERWERKE GMBH) 16 October 1996 (1996-10-16) the whole document ---	1-6
X	US 4 832 836 A (SELSDON LESLIE) 23 May 1989 (1989-05-23) column 2 column 6, line 9 - line 37 column 9, line 60 - column 10, line 19 figures 1,2,9 ---	1
A	EP 0 678 318 A (REUSCHLING WALTER) 25 October 1995 (1995-10-25) figure 1 ---	1-6
A	US 2 525 287 A (CUNO CHARLES H) 10 October 1950 (1950-10-10) figure 1 ---	1-6
	--- -/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

7 January 2004

Date of mailing of the international search report

14/01/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Hilt, D

## INTERNATIONAL SEARCH REPORT

Intern Application No  
PCT/IB 03/04079

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 970 557 A (SHOUP STEPHEN G) 20 July 1976 (1976-07-20) column 2; figures ---	1-6
A	WO 01 07142 A (NIEUWLAND PIERRE GERARD WILLEM ;NTZ INTERNAT HOLDING B V (NL)) 1 February 2001 (2001-02-01) figures -----	1-6

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 03/04079

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0737502	A	16-10-1996	DE 19514224 A1 DE 59600295 D1 EP 0737502 A2	17-10-1996 30-07-1998 16-10-1996
US 4832836	A	23-05-1989	GB 2141354 A , B GB 2168262 A	19-12-1984 18-06-1986
EP 0678318	A	25-10-1995	DE 4413589 A1 DE 9421990 U1 EP 0678318 A2	26-10-1995 10-07-1997 25-10-1995
US 2525287	A	10-10-1950	NONE	
US 3970557	A	20-07-1976	GB 1466805 A JP 50096974 A JP 57018930 B	09-03-1977 01-08-1975 20-04-1982
WO 0107142	A	01-02-2001	NL 1012700 C1 AU 6322600 A BR 0012769 A CN 1365297 T EP 1198278 A1 JP 2003505228 T WO 0107142 A1 US 6536600 B1	16-09-1999 13-02-2001 02-04-2002 21-08-2002 24-04-2002 12-02-2003 01-02-2001 25-03-2003

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record.**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**